er ▓▓▓▓▓ "real time" "non real time"

Advanced search

Search   About 18,300 results (0.08 seconds)

Everything

Images

Maps

Videos

News

Shopping

More

Alexandria, VA
Change location

All results
Related searches
More search tools

» **Real-time** operating system - Wikipedia, the free encyclopedia
en.wikipedia.org/wiki/Real-time_operating_system - Cached
Key factors in a **real-time** OS are minimal **interrupt** latency and minimal ... **real- time** tasks share computing resources with many **non-real-time** tasks, ... Such mechanisms involve system calls, and usually invoke the OS's **dispatcher** code on exit, ... **queues** work to be done at a lower priority level, such as unblocking a **driver** ...

Method and apparatus for performing **real-time commands in a non** ...
www.patsnap.com/patents/view/US20060060708.html - Cached
The method as claimed in claim 1, wherein said **non real time** operating system .... 2, the device **driver** 5 comprises a **command dispatcher** 4, a command **queue** 6, ... [0045] While in the preferred embodiment an **interrupt** is understood to be ...

[PDF] A Survey of **Real-time** Operating Systems
www.ece.stevens-tech.edu/~ymeng/courses/CPE555/papers/rtos_paper.pdf
File Format: PDF/Adobe Acrobat - Quick View
Real-time applications have the requirement to meet task deadlines in .... **Interrupt dispatch** latency: This is the time to go from the last instruction in the **interrupt** .... **command** schedules a process based on time or an event; SIGNAL and .... systems to help isolate **real-time** activities from **non-real-time** activities of the operating ...

Method and apparatus for performing **real-time commands in a non** ...
www.freepatentsonline.com/y2006/0060708.html - Cached
Mar 17, 2005 -- Software and hardware **interrupts** can cause the operating system to give ... The **command dispatcher** 4 orders the received commands in a **queue** 6 and .... Usually, in a **non-real time** operating system, the device **driver** is ...

VxWorks - Device **Driver** Development
studies.ac.upc.edu/doctoral/ENGRAP/VxWorks-
device-drivers.htm - Cached
Operating systems can be categorized into **real-time**
and **non-real-time** systems. ... to as the **dispatcher**,
has a significant impact on the responsiveness of the
OS. ... Multiple tasks can wait on a single message
queue and can be ordered by their ... Many real world
drivers just have an **interrupt** handler and interact
with user ...

[PDF] **Real-Time** Handling of GPU **Interrupts**
in LITMUS
www.cs.unc.edu/~anderson/papers/rtss11d.pdf
File Format: PDF/Adobe Acrobat - Quick View
by GA Elliott - Cited by 1 - Related articles
have **non-real-time**, throughput-oriented, closed-
source device **drivers** into an actual **real-time**
operating sys- tem [12] on a multiprocessor platform.
The non- real ...

[PDF] A Comparison of Windows **Driver** Model
Latency Performance on ...
www.usenix.org/events/osdi99/full_papers/cota/cota.pdf
File Format: PDF/Adobe Acrobat - Quick View
by E Cota-Robles - Cited by 40 - Related articles
the **driver** uses thread-based or **interrupt**-based
processing. ... concurrent **non- real-time** computation
and by using a **real-time** OS ..... the worst-case
thread **dispatch** latency for a thread waiting on ...
Because ordinary DPCs **queue** in FIFO order, DPC
latency ... **drivers** have simple **command** line control
applications and use ...

FAQs - Xenomai
www.xenomai.org/index.php/FAQs - Cached
Jan 14, 2011 – Adeos implements an **interrupt**
pipeline at its core to **dispatch** events in a .... you
may modify the **non real-time driver** which shares an
IRQ with a ...

[PDF] Sun Java **Real-Time** System 2.0: A
Deep Dive + Some Random Stuff
java.sun.com/javase/technologies/realtime/pdf/bollella_deepdive.rs.pdf
File Format: PDF/Adobe Acrobat - Quick View
Priorities / **Dispatcher** semantics. • Processor
Affinity / **Interrupt** Handler Management. •
waitForNextPeriod() ... >Enhanced predictability with
additional Cyclic **driver**. • Predictability via ...
Throughput. Data Transfer **Queues** ... Preserves
performance for **non real-time** logic ... Java RTS has
a **command**-line option to output an ...

[PDF] **Real-Time** Linux
www.aeolean.com/html/RealTimeLinux/RealTimeLinuxReport
-2.0.0.pdf
File Format: PDF/Adobe Acrobat - Quick View
report cannot capture every possible detail and facet
of the **real-time** Linux computing world, ... B.2 **Real-
Time** Linux **Support** Organizations . .... that only
handles **interrupt dispatching**. ... **Non Real Time** ....
and unloaded into the kernel space by user-space
commands ..... such as **queues**, semaphores or
memory regions. ...

1 2 3 4 5 6 7 8 9 10   Next

Search Help   Give us feedback

Google Home   Advertising Programs   Business Solutions   Privacy   About Google